


Partner



Lorenzoni Srl

Soc. Unipersonale
Via Molini 98/3
36055 Nove (VI) Italy
P.IVA e C.F. 02872270240
R.I. 02872270240 – R.E.A. 280950

CAVI SCALDANTI – RESISTENZE ELETTRICHE – TERMOREGOLAZIONE
HEATING CABLES- HEATING ELEMENTS – TERMOREGOLATION

Tel. +39 0424 502042
Fax + 39 0424 502043
info@lorenzoni-srl.it
www.lorenzoniheaters.com

CONTROL DIGITAL PANEL IP65

230 VAC 1PH

ORDER CODE 523.0000.140

PROCESS CONTROL – DATA SHEET

EASY TO INSTALL AND TO USE


THIS PANEL IS IDEAL TO CONTROL YOUR HEATING EQUIPMENT



APPLICATION

- ANTIFREEZE SAFETY
- OUTDOOR POOLS
- WATER NETWORKS
- CONTROL OF ANTIFREEZE RESISTANCES
- CONTROL OF HEATING ELEMENTS
- CONTROL OF POWER PANELS IN THE FOOD PROCESSING INDUSTRY AND IN LABORATORIES
- FOR MOULD-PRONE ENVIRONMENTS WHICH HAVE TO BE WASHED FREQUENTLY
- ETC ...

Partner



Lorenzoni Srl

Soc. Unipersonale
Via Molini 98/3
36055 Nove (VI) Italy
P.IVA e C.F. 02872270240
R.I. 02872270240 – R.E.A. 280950

CAVI SCALDANTI – RESISTENZE ELETTRICHE – TERMOREGOLAZIONE
HEATING CABLES- HEATING ELEMENTS – TERMOREGULATION

Tel. +39 0424 502042
Fax + 39 0424 502043
info@lorenzoni-srl.it
www.lorenzoniheaters.com

TECHNICAL DATA

- VOLTAGE: 230 V 1PH
- POWER MAX: 3.5 KW
- FRONT PROTECTION: IP65, WASHABLE
- EQUIPPED WITH A BIPOLAR CIRCUIT BREAKER 20 A + CONTACTOR + 1 REGULATOR ON THE FRONT
- CONFIGURABLE PT100 SENSOR OR THERMOCOUPLE TYPE K OR J
- TYPE OF CONTROL: ON/OFF OR PID WITH THE POSSIBILITY OF TIMER RAMP/PROCESSING AND SMOOTH START, AS WELL AS AUTO-ADJUSTMENT
- 3 ALARMS POSSIBLE: HIGH AND LOW, DEVIATION HIGH, LOW OR BAND, SENSOR FAILURE WITH STORAGE POSSIBILITY
- FRONT DIMENSIONS: 192 X 164 MM, DEPTH 105 MM
- MOUNTING: WALL MOUNTING WITH INCLUDED MOUNTING KIT
- 3 MOUNTED CABLE GLANDS
- TEMPERATURE OF USE: FROM -5 TO 50°C
- STORAGE TEMPERATURE: FROM -10 TO 60°C
- USAGE AND STORAGE AMBIENT HUMIDITY: FROM 10 TO 90% RH NON-CODENSING
- DATA IS DISPLAYED WITH A RESOLUTION OF 1/10/2 DISPLAYS OF 4 DIGITS, 2 COLOURS EASY-READ DISPLAY + ACTIVE ALARM SETPOINT STATUS LIGHTS

